

METHOD AND APPARATUS FOR AUTOMATICALLY GENERATING A TERRAIN MODEL FOR DISPLAY DURING FLIGHT SIMULATION

FIELD OF THE INVENTION

The present invention relates generally to methods and apparatus associated with flight simulation and, more particularly, to methods and apparatus for generating a terrain model for display during flight simulation.

5 BACKGROUND OF THE INVENTION

10 Pilots frequently wish to simulate a mission prior to actually flying the mission. By simulating the mission, a pilot can become familiar with the mission route and can either avoid or prepare in advance for any portions of the mission that may require special effort or attention. In order to simulate a mission route, a pilot initially defines the mission route, such as by means of a mission planning system (MPS) or the like. As known to those skilled in the art, a mission planning system receives input from a pilot that defines a plurality of points along the mission route. For example, the pilot typically defines the beginning and end point(s) of the mission as well as points along the route at which the aircraft will
15 change direction. The pilot also defines points that identify the location of targets or other features of interest. In addition to merely entering the points, the pilot also indicates the significance of each point, such as by indicating that the point represents an airfield, a target, a point at which the aircraft will change direction or the like. Based upon the plurality of points defined by the pilot, the MPS
20 constructs the mission route to include each of the plurality of points.

Once the pilot has defined the mission route, a terrain model designer determines the area for which terrain source data will be required. In this regard, terrain source data is typically obtained, not just along the mission route, but for some distance on either side of the mission route to permit the flight simulation to
25 continue if the aircraft deviates from the mission route. The size of the area for which terrain source data is required is typically based, in part, upon the aircraft platform including the range of the sensors onboard the aircraft, the turning radius of the aircraft and any other aircraft parameter that affects the size of the area that will be viewed by the pilot or interrogated by the aircraft and its sensors. In this
30 regard, some aircraft platforms are capable of gathering and analyzing more

remote sensor data than other aircraft platforms and therefore generally require terrain source data to be collected for larger areas surrounding the mission route in order to properly simulate the planned mission.

5 Additionally, the terrain model designer must determine the resolution with which the terrain source data should be displayed. Typically, different portions of the terrain source data are displayed at different resolutions, each of which is typically defined by the terrain model designer. In this regard, the images in the vicinity of an airfield, a target or other feature of interest are generally defined with greater resolution than more general terrain that is somewhat removed from the mission route.

10 As described above, the terrain model designer must therefore determine the area for which terrain source data is required and the respective resolution of each different region within the area for which terrain source data is required in order to permit the proper images to subsequently be generated and presented to the pilot during flight simulation. As will be apparent, the determination of the area for which terrain source data is required and the respective resolution of each region within that area is not only a time-consuming task, but is also prone to errors.

15 Based upon the definition of the area, a terrain model designer then collects the terrain source data required to construct a terrain model for a simulated flight along the mission route. Among other things, the terrain source data includes digitized photographs of the area over which the mission route will be flown. In addition to imagery, the terrain source data includes elevational data defining the elevation of the terrain along the mission route and feature data defining a variety of features, including obstructions, targets and the like, along the mission route.

20 The terrain model designer can collect at least some of the terrain source data from terrain source data that is stored in a local memory device. However, the terrain model designer oftentimes must collect additional terrain source data for areas along the mission route for which no terrain source data is locally stored.

25 Additionally, even in instances in which the terrain source data is stored in a local memory device, the terrain model designer typically canvasses other sources of terrain source data to determine the availability of terrain source data that is of higher quality and/or more recent than the terrain source data that is stored in a local memory device. If terrain source data that is of higher quality and/or more

30

recent is available, the terrain model designer will generally obtain the higher quality terrain source data for use during the flight simulation in lieu of the terrain source data that is already stored by a local memory device, but that is of a lower quality and/or is less recent.

5 Electronic collections of terrain source data are maintained by a variety of sources. For example, terrain source data may be available from the joint services imaging processing station (JSIPS), the Gateway Data Navigator (GDN), the United States Imagery and Geospatial Information Services (USIGS), the master environment library (MEL), weather service feeds, commercial databases and the like. For many of these sources, however, the terrain model designer must
10 complete and submit appropriate documents requesting the terrain source data and, in some instances, must provide proof that the terrain model designer as well as the pilots and other personnel who will have access to the terrain source data have appropriate clearances to access and view the terrain source data. As will be
15 apparent, the process of searching, collecting and assimilating the terrain source data can also be a time-consuming process.

 Once the terrain source data has been collected, the terrain source data is generally processed in order to improve or refine the resulting image and to extract various features from the terrain source data. In this regard, software programs,
20 such as the Imagine software package by ERDAS, Inc. of Atlanta, Georgia, provide many standard image processing functions, such as image enhancement, image registration, image rectification, image mosaic functions and elevation extraction. Additionally, these conventional software programs provide two-dimensional feature extraction and three-dimensional feature extrusion as well as
25 material classification. While these conventional software programs perform the various image processing and feature extraction functions, the terrain model designer must generally provide the proper data in the correct format and must manually initiate and interact with the software program to perform the desired image processing.

30 Following the image processing operations, the terrain model designer provides the terrain source data to a terrain modeling software. The terrain modeling software compiles the terrain source data to form a terrain model. As with image processing, a variety of software programs, such as the Terra Vista software package from Terrain Experts, Inc. of Tucson, Arizona, are commercially

available for generating a terrain model based upon terrain source data. The terrain model can then be provided to a flight simulator and, more particularly, to the image generator of a flight simulator for generating the necessary images during a simulation of the mission by the pilot.

5 While the terrain model that is necessary to simulate the mission to be flown by the pilot can be constructed in the manner described above, the manual process of collecting and processing the terrain source data and constructing the terrain model is time-consuming and requires that the terrain model designer have substantial experience. For example, the terrain model designer must often locate
10 and obtain terrain source data from a variety of different collections. In addition, the terrain model designer must oftentimes determine the area for which terrain source data is to be collected and the resolution of the terrain source data for different regions within the area in order to properly simulate the mission route with the desired degree of detail. As such, it would be desirable to develop an
15 improved method and apparatus for generating the terrain model for display during a simulated flight along a predefined mission route that could reliably and accurately generate the terrain model in a more efficient manner while requiring less manual intervention.

SUMMARY OF THE INVENTION

20 A method and apparatus are provided for automatically generating a terrain model for display during a simulated flight along a predefined mission route. By automatically generating the terrain model, the method and apparatus of the present invention are more efficient than conventional techniques for generating terrain models that require extensive manual participation. The method and
25 apparatus of one advantageous embodiment also automatically collect and combine project source data with the terrain source data such that the resulting terrain model is an accurate depiction of the area through which the mission will be flown.

 The apparatus for automatically generating the terrain model includes a mission profiler. The mission profiler automatically determines the area
30 containing the mission route for which the terrain source data is required. According to one embodiment, the mission profiler includes an input for receiving data at least partially defining the mission route. Additionally, the mission profiler of this embodiment includes a processing element for automatically determining

the area containing the mission route for which terrain source data is required. The processing element also automatically divides the area into a plurality of regions based upon the mission route and determines the respective resolution of the terrain source data for each region.

5 The processing element is typically capable of determining the area and the respective resolution of regions within the area based upon predefined criteria. In one embodiment, the input of the mission profiler can receive adjustments to at least some of the predefined criteria such that the processing element will, instead, determine the area and the respective resolution of regions within the area based
10 upon the adjusted criteria. The input of the mission profiler can also receive data defining the aircraft platform and/or the simulator platform. As such, the processing element can determine the area and the respective resolution of regions within the area based at least partially upon the aircraft platform and/or the simulator platform. The input of the mission profiler can also receive data defining
15 a plurality of different types of points along the mission route. In this embodiment, the processing element determines the area and the respective resolution of regions within the area based at least in part upon the different types of points along the mission route, such as points designating an airfield, a target or the like.

 The apparatus for automatically generating a terrain model can also include
20 an apparatus for automatically collecting terrain source data for display during flight simulation. The apparatus for automatically collecting terrain source data includes a search engine for automatically searching a plurality of electronic collections of terrain source data to identify terrain source data covering the area containing the mission route. The apparatus for automatically collecting terrain
25 source data also includes an input for receiving data defining the area containing the mission route for which terrain source data is required and a memory device for storing the terrain source data covering the area containing the mission route that has been identified by the search engine.

 The memory device typically stores terrain source data from prior mission
30 routes. During the process of automatically searching the electronic collections of terrain source data, the search engine preferably compares the terrain source data obtained from the electronic collection(s) with terrain source data from prior mission routes to identify the terrain source data that is most acceptable for the flight simulation for the mission route. For example, the search engine may select

the terrain source data that is of the highest quality and/or is the most recent. In one embodiment, the search engine does not initially obtain the terrain source data itself. Instead, the search engine of this embodiment obtains information representative of the terrain source data that is obtainable from the electronic collection(s). This information is generally termed "metadata". The search engine then obtains only that terrain source data from the electronic collection(s) that is more acceptable for the flight simulation of the mission route than the terrain source data from prior mission routes that is already stored by the memory device. Thus, the method and apparatus of this embodiment only collect the additional terrain source data that is required to depict the area containing the mission route, thereby increasing the efficiency with which the terrain source data is collected.

The memory device preferably stores the terrain source data that is obtained from the electronic collection(s). In one embodiment, the memory device can therefore include a first memory device for storing information representative of the terrain source data and a second memory device for storing the terrain source data itself.

The apparatus for automatically generating a terrain model also includes an image engine for processing terrain source data into one or more predefined formats. In this regard, the image engine automatically generates processed terrain data having one of the predefined formats and, typically, at least one of a corrected elevation model, a material map, vector data and a feature model.

The apparatus for automatically generating a terrain model further includes a terrain engine for automatically compiling the processed data to create a terrain model for display during flight simulation. In this embodiment, the terrain engine includes a data importer for receiving the processed data for the area containing the mission route. For example, the processed data can include imagery data, elevational data, feature data and/or mission route data. The data importer also receives project source data defining geospecific properties for the area containing the mission route. For example, the project source data can include information related to vegetation and/or cultural features. The terrain engine also includes a terrain compiler for automatically creating the terrain model for display during flight simulation based upon a combination of both the processed data and the project source data. The resulting terrain model can then be provided to a flight

simulator and, more particularly, the image generator of a flight simulator for generating the requisite image during simulation of the mission.

In addition to the apparatus for automatically generating the terrain model, a corresponding method is also provided. Similarly, corresponding methods for automatically determining the flight simulation mission profile, for automatically collecting terrain source data, for automatically processing the terrain source data into one or more predefined formats and for automatically compiling the processed data to create a terrain model are also provided. As a result of the automatic generation of the terrain model, the method and apparatus of the present invention permit the terrain model to be more efficiently generated with substantially less manual participation than conventional techniques. Additionally, the resulting terrain model should be of the highest quality since the terrain source data that is most acceptable, typically by being of the highest quality and/or the most recent, is collected and compiled to create the terrain model. Moreover, the terrain model may also be partially based upon project source data to further improve the realistic appearance of the resulting terrain model.

BRIEF DESCRIPTION OF THE DRAWINGS

Having thus described the invention in general terms, reference will now be made to the accompanying drawings, which are not necessarily drawn to scale, and wherein:

Figure 1 is a block diagram of an apparatus for automatically generating a terrain model for display during a simulated flight along a predefined mission route according to one embodiment of the present invention;

Figure 2 is a graphical representation of a mission route;

Figure 3 is a graphical representation of the area containing the mission route for which terrain source data is required and the respective resolution of different regions within the area as determined by a mission profiler according to one embodiment of the present invention;

Figure 4 is a flow chart illustrating the operations performed by a method and apparatus for automatically collecting terrain source data including a search engine according to one embodiment of the present invention;

Figure 5 is a graphical representation of an image engine according to one embodiment of the present invention for processing the terrain source data into one or more predefined formats that may be accepted by the terrain engine;

Figure 6 is a block diagram of a terrain engine for automatically compiling terrain source data and project source data to create the terrain model for display during flight simulation according to one embodiment of the present invention; and

Figure 7 is a block diagram illustrating an apparatus for automatically generating the terrain model during a simulated flight along the predefined mission route according to one embodiment of the present invention which includes a plurality of parallel channels.

DETAILED DESCRIPTION OF THE INVENTION

The present invention now will be described more fully hereinafter with reference to the accompanying drawings, in which preferred embodiments of the invention are shown. This invention may, however, be embodied in many different forms and should not be construed as limited to the embodiments set forth herein; rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the invention to those skilled in the art. Like numbers refer to like elements throughout.

Referring now to Figure 1, an apparatus 10 for automatically generating a terrain model for display during a simulated flight along a predefined mission route is depicted. Although the upcoming flight to be simulated will be consistently referred to as a mission, the upcoming flight need not necessarily be a military exercise, but can be a commercial flight or a flight taken for other reasons, such as pleasure. The mission route can be defined in a variety of different manners. However, the mission route is commonly provided by a mission planning system (MPS) 12.

In order to define a mission route, a pilot initially provides the MPS 12 with a description of the general geographic region within which the mission will be flown. The MPS will then display a two-dimensional representation of a map of the geographic region. The pilot will then plot the mission route upon the map in a manner known to those skilled in the art. For example, the pilot can identify specific points along the mission route by sequentially positioning a cursor at each respective point and then providing an indication, such as by depressing the enter

key or the like, that the current position of the cursor identifies a point along the mission route. Based upon the location of the points identified upon the map, the MPS can determine the latitude and longitude of each point to facilitate construction of the mission route. Instead of selecting points upon the map to be indicative of points along the mission route, however, the pilot can directly enter the latitude and longitude of points along the mission route, if known.

Based upon the points identified by the pilot, the MPS 12 constructs the mission route as depicted in Figure 2. In addition to merely designating points along the route for purposes of the construction of the mission route, the pilot can identify characteristics associated with each of the points. For example, the pilot can indicate if the point represents the location of an airfield, such as the airfield from which the aircraft is taking off and/or landing. Additionally, the pilot can indicate points along the mission route that are targets as well as points along the mission route at which the aircraft will turn or otherwise change course. The MPS records the additional information associated with respective points along the mission route. Additionally, the MPS can display icons associated with each point along the mission route to represent the characteristics associated with the point. For example, the MPS can present points associated with the starting point, targets and turns with different icons, such as the home plate and square icons, the triangular icon and the circular icon, respectively, in Figure 2.

Once the pilot, in conjunction with the MPS 12, has defined the mission route, the MPS provides the mission route to the apparatus 10 of the present invention such that a terrain model can be automatically generated for subsequent display during a simulated flight along the predefined mission route. In this regard, the MPS typically provides the apparatus with the coordinates that define the various segments of the mission route as well as data defining characteristics associated with the respective points as described above. As shown in Figure 1, the apparatus of the present invention includes a mission profiler 14 that initially receives the data provided by the MPS that defines the mission route. The mission profiler automatically determines the area that contains the mission route for which terrain source data is required. That is, the mission profiler automatically identifies the area along the mission route as well as areas in the vicinity of the route that may be viewed during flight simulation, either by the pilot or by onboard sensors, and for which terrain source data is required.

The automated mission profiler 14 includes an input 16 for receiving data at least partially defining the mission route. In this regard, the input receives data from the MPS 12 that defines the mission route entered by the pilot, typically in terms of the coordinates of points along the mission route as well as characteristics associated with various ones of the points. The automated mission profiler also includes a processing element 18 for automatically determining the area containing the mission route for which imagery data is required. The processing element automatically determines the area for which terrain source data is required based upon a plurality of parameters. For example, the processing element can determine the area for which terrain source data is required based, at least in part, upon data defining the aircraft platform and/or the simulator platform. In this regard, the data defining the aircraft platform generally includes data defining the ranges of the various sensors onboard the aircraft, data defining the turning radius of the aircraft at various speeds and other data that defines parameters that could effect the area that the pilot will view or the onboard sensors or subsystems will interrogate during the subsequent flight simulation. In this regard, aircraft platforms having sensors with larger ranges will generally require the mission profiler to define a larger area than aircraft platforms having sensors with smaller ranges. Likewise, aircraft platforms having a larger turning radius will generally dictate that the mission profiler define a larger area for those portions of the area in which the aircraft will turn than aircraft platforms with a smaller turning radius. For each different aircraft platform, the mission profiler is therefore typically designed to define an area of a predetermined size, typically by extending both starboard and port from the mission route by a predefined distance.

The mission profiler 14 also defines the area for which terrain source data is required based upon the different types of points along the mission route. Therefore, for a respective aircraft platform, the mission profiler generally defines the area to extend a predefined distance to both the starboard and the port sides of the aircraft from the mission route. The mission profiler then modifies the area for which terrain source data is required based upon the different types of points along the mission route. For example, the area for which terrain source data is required is generally increased in regions surrounding the points that are indicative of a turn or a change in course of the mission route. For example, based upon a respective aircraft platform traveling at a predetermined speed, the mission profiler preferably

increases the area by a predetermined amount in those regions in which the aircraft will turn. Based upon the mission route including the plurality of different types of points along the mission route and the aircraft platform, the mission profiler therefore refines the area for which terrain source data is required.

5 The processing element **18** of the mission profiler **14** also automatically divides the area into a plurality of regions based upon the mission route and determines a respective resolution of the terrain source data for each region. In this regard, the mission profiler generally defines a predetermined baseline resolution for the terrain source data, typically in units of meters or submeters. For certain
10 regions of the area, however, the mission profiler will dictate that the terrain source data be provided with increased resolution in order to permit the pilot to view additional details of the region during the subsequent flight simulation. For example, those regions that surround a target or an airfield preferably have a greater resolution.

15 By way of example, a graphical depiction of the area for which terrain source data will be provided in conjunction with the mission route of Figure 2 is depicted in Figure 3. The graphical display of Figure 3 also indicates that the area for which terrain source data is provided has been divided into two regions of different resolution. In this regard, the centrally located tiles having a lighter color
20 have a greater resolution than the surrounding tiles having a darker color. For point of reference, the mission route is also plotted upon the graphical representation of the area for which terrain source data is provided to graphically depict relative sizes of the area for which imagery data will be provided with respect to the mission route.

25 The mission profiler **14** preferably defines each region to have a respective resolution. However, the input **16** of the mission profiler can also receive data defining the simulated platform upon which the terrain model constructed from the terrain source data will subsequently be displayed. As known to those skilled in the art, a flight simulator generally has an image generator that receives and
30 processes a terrain model to produce the plurality of images displayed for the pilot during flight simulation. The image generators of different types of flight simulators have different processing capabilities. As such, the data provided to the mission profiler regarding the simulator platform provides an indication of the processing capabilities of the image generator. In instances in which the data

indicates that the image generator of the flight simulator will be unable to effectively process a terrain model having increased resolution, the mission profiler will generally reduce the resolution of at least some and, more typically, all of the regions such that the resulting terrain model can be processed by the image generator. By somewhat reducing the resolution of at least some of the regions, the mission profiler prevents the generation of unnecessarily high resolution terrain models that will go unused by the flight simulator.

As described above, the mission profiler **14** is configured to define an area of a predetermined size relative to the mission route and to divide the area into regions of different predetermined resolutions, also based upon predefined criteria. The mission profiler of one advantageous embodiment permits a technician, a pilot or the like to adjust the predefined criteria, however, in order to adjust the size of the area for which terrain source data will be provided and to adjust the respective resolutions of different regions within the area. For example, a pilot may enlarge the area and increase the resolution of each region within the area by a predetermined percentage in order to make the subsequent flight simulation even more realistic.

The input **16** and the processing element **18** of the mission profiler **14** are typically comprised of a processor or other type of computing device for executing a computer program that provides the functionality of the mission profiler as described above. The computer program can be either embedded within the processing element or may be stored by a memory device external to and accessible by the processor or other computing device.

Once the mission profiler **14** has determined the area for which terrain source data is required and the respective resolution of different regions within the area, the mission profiler provides this information to an apparatus **20** for automatically collecting terrain source data for display during flight simulation. See Figure 1. In this regard, the apparatus for automatically collecting terrain source data includes an input **22** for receiving the data provided by the mission profiler that defines the area containing the mission route for which terrain source data is required. Additionally, the input preferably receives the data provided by the mission profiler that defines the respective resolution of different regions within the area. See block **50** of Figure 4.

The apparatus **20** for automatically collecting terrain source data also includes a search engine **24** for automatically searching a plurality of electronic collections **25** of terrain source data to identify terrain source data covering the area containing the mission route. See block **52**. As known to those skilled in the art, a variety of electronic collections of terrain source data are maintained, both by governmental and commercial entities. Although the search engine can search any of the electronic collections of terrain source data, the search engine preferably searches those collections that have been approved by the national agencies. In one embodiment, for example, the search engine searches the electronic collections of terrain source data maintained by JSIPS, USIGS and MEL. In addition, the search engine of this embodiment can search the electronic collection of terrain source data provided by the National Weather Service, the United States Geological Survey (USGS) and by commercial satellites, such as IKONOS, LandSat, SPOT and the like.

The search engine **24** searches the electronic collections **25** of terrain source data to identify terrain source data that covers all, or at least the greatest percentage of, the area containing the mission route. In searching the electronic collections of terrain source data, the search engine will oftentimes identify terrain source data maintained by different electronic collections that depict the same portion of the area. In these instances, the search engine reviews the terrain source data from each electronic collection and selects the terrain source data that is of the highest quality and is most recent. For example, the search engine will select a digital photograph of a portion of the area taken on a clear day in the past week instead of a digital photograph of the same portion of the area taken on an overcast day two months ago, assuming that the mission is intended to be performed on a clear day. As such, the digital photograph taken on a clear day will be more representative of the situation with which the pilot will actually be confronted during the flight.

In addition to the search engine **24**, the apparatus **20** for automatically collecting terrain source data also includes a memory device **26**. Among other things, the memory device preferably stores terrain source data from prior mission routes. As such, the search engine not only searches the electronic collections **25** of terrain source data maintained by governmental and commercial entities, but also preferably searches the memory device for terrain source data covering all or a

portion of the area for which terrain source data is required. In instances in which the memory device includes terrain source data for at least a portion of the area for which terrain source data is required, the search engine preferably also searches the electronic collections of terrain source data maintained by governmental and commercial entities to determine if the terrain source data maintained by these electronic collections is of higher quality or more recent than the terrain source data stored by the memory device. If the electronic collections of terrain source data maintained by governmental or commercial entities is of higher quality than the terrain source data stored by the associated memory device, the search engine will obtain the terrain source data from the electronic collections and, as such, will not use the terrain source data stored by the memory device. If, however, the terrain source data stored by the memory device is of equal to or better quality than the terrain source data maintained by the electronic collections, the search engine will not obtain the data from the electronic collections and will, instead, utilize the terrain source data stored by the memory device since the terrain source data stored by the memory device can be accessed more efficiently. See blocks 56 and 58 of Figure 4.

Typically, the search engine 24 does not initially obtain the terrain source data. Instead, the search engine preferably initially obtains information representative of the terrain source data. This information that is representative of the terrain source data is commonly termed "metadata". The metadata typically defines the geographical region covered by the associated terrain source data and indicates the type of terrain source data, such as a digital photograph or the like, and the date on which the terrain source data was obtained. In addition, the metadata may provide an indication of the conditions under which the terrain source data was obtained, such as cloudy, clear, rainy or the like. See block 54 of Figure 4. Based upon the metadata, the search engine can identify terrain source data that covers the entire area for which terrain source data is required and can determine the terrain source data that will provide the highest quality image of the area.

By initially obtaining and reviewing information, such as metadata, representative of the terrain source data, however, the search engine 24 can more efficiently perform the search and analysis process than if the search engine obtained the terrain source data itself. In this regard, the metadata is typically a

much smaller quantity of data than the associated terrain source data. As such, the metadata can be much more efficiently transferred and analyzed than the terrain source data.

5 Once a search engine **24** identifies the terrain source data maintained by one or more electronic collections **25** that is required in order to provide the highest quality terrain source data for the area, the terrain source data is obtained and stored by the memory device **26**. See block **60**. Although the memory device can be constructed in various manners, the memory device is typically comprised of first and second memory devices **26a**, **26b**. In this regard, the first memory
10 device, such as a simple query language (SQL) database, typically stores the information, such as the metadata, representative of the terrain source data, while a second memory device, such as a mass storage system, stores the terrain source data itself. In order to efficiently locate the terrain source data within the second memory device, the first memory device can also store pointers or addresses for
15 identifying the terrain source data associated with the metadata.

The input **22** and the search engine **24** are typically comprised of computer software that is supported and executed by a dedicated server. However, the computer software that generally comprises the input and the search engine can be supported and executed by a processor or other computing device, if so desired.

20 Once the terrain source data has been collected, the method and apparatus **10** of the present invention automatically process the terrain source data to refine the resulting image and to extract various features therefrom. As a result of this processing, the terrain source data is transformed into one or more predefined formats that can be subsequently accepted by the terrain engine, as described
25 below. This automatic processing is typically performed by an image engine with the computer software that embodies the image engine typically being supported and executed by a processor or other computing device.

While the image engine **28** can perform any of a variety of conventional image processing techniques in order to refine the resulting data, the image engine
30 of one embodiment performs an image enhancement function as shown in block **70** of Figure 5 in order to perform atmospheric corrections. Additionally, the image engine can perform image registration of the enhanced image in order to register the images to fixed points. See block **72**. Furthermore, the image engine can provide an elevation extraction function in order to generate an elevation model.

See block 74. In this regard, the image engine or a memory device associated therewith typically includes a relatively low resolution elevation model of at least the geographic region surrounding the mission route. Based upon stereo pairs of the terrain source data, such as pairs of digital photographs that at least partially overlap, the elevation extraction function can extract elevation information in order to revise the low resolution elevation model to include the elevation of features above ground level, such as trees, buildings and the like.

Further, the image engine **28** can perform image rectification upon the registered image in order to remove image distortion and to make the resulting image square. See block **76** of Figure 5. Following image rectification, the image engine can perform an image resolution merge in which the resulting image produced by the image rectification function is merged with low resolution imagery, typically provided by the second memory device **26b**. See block **77**. As such, higher resolution black and white images may be combined with lower resolution color images to create higher resolution color images. The image engine then performs an image mosaic function in order to merge a plurality of overlapping images and an image tonal balance function to balance the colors therebetween, thereby creating the resulting imagery data. See blocks **78** and **79**.

Additionally, a material set **80** that defines the different types of materials, such as concrete, trees, wood, etc., that may be visible in the imagery data is provided. Based upon the imagery data and the material set, the image engine can perform a material classification function in order to generate a material map that defines the material type of various features in the imagery data. See block **82**. The material map can then be provided to the various simulated sensors, such as the radar and the infrared sensors, onboard the aircraft platform such that the readings of the sensors will properly simulate actual flight conditions. The image engine can also extract two-dimensional features from the terrain source data in order to generate vector data based upon not only the terrain source data, but also the material map and low resolution feature data, typically provided by the second memory device **26b**. See block **84**. The two-dimensional feature data generally defines the features present in the imagery data when viewed from above. This vector data can be utilized to correct the elevation model in order to remove features that extend above ground level to generate a corrected elevation model representative of the elevation of the terrain itself, and not buildings, trees and the

like that extend above ground level. See block 86. Finally, the image engine can perform a three-dimensional culture generation based upon the imagery data, the vector data and the output of the elevation extraction function in order to perform a three-dimensional feature extrusion function, thereby generating feature models.

5 See block 88. In this regard, the three-dimensional feature extrusion function generates three-dimensional models of various features, such as trees, buildings, bridges and the like, that are represented in two-dimensions in the imagery data. The three-dimensional models can then be utilized to provide a more realistic simulation. The image engine of this embodiment therefore generates imagery
10 data, a corrected elevation model, vector data, a feature model and a material map, each of which are stored by the memory device 26, more particularly, by the second memory device 26b.

While the individual image processing functions described above may be separately performed by a commercial software package entitled Imagine available
15 from ERDAS, Inc. of Atlanta, Georgia, the foregoing image processing functions have not previously been performed in an automated and integrated manner than minimizes, if not eliminates, manual interaction as provided by the image engine of the present invention. In addition, while one exemplary set of image processing functions has been described above, the method and apparatus 10 of the present
20 invention can include other types of image engines 28 for performing a different sequence or set of image processing functions, if so desired.

The method and apparatus 10 of the present invention also includes a terrain engine 30 for compiling the processed data following image processing to create a terrain model for display during a subsequent flight simulation. As shown
25 in Figure 6, the terrain engine includes a data importer 32 for receiving processed data for the area containing the mission route. As described above, the processed data can include imagery data and one or more of a corrected elevation model, vector data, feature models and a material map. According to one advantageous embodiment, the data importer also receives project source data. The project
30 source data has typically been previously stored in the memory device 26 and defines geospecific properties for the area containing the mission route. For example, the project source data can include information related to vegetation and information related to cultural features. The information related to vegetation may indicate that the area includes a large number of a particular type of tree having a

specific color. As such, the color of the resulting image can be adjusted to ensure that the vegetation is properly depicted. Similarly, the information related to cultural features can include data that indicates that the area is chiefly covered by sand having a particular color. As such, the color of the resulting image can also be adjusted to ensure that the sand is properly depicted in order to permit a more realistic image to be generated. In addition to the data importer, the terrain engine also generally includes a terrain compiler 34 for combining the processed data and the project source data to create a terrain model that is stored in a database 35. In this regard, the terrain model is preferably stored in the format that will be acceptable to the simulation platform that will subsequently process and display the terrain model.

In addition to providing a terrain model, the terrain engine 30 can include a radar compiler for further processing the terrain model to generate a radar model that can utilized during a subsequent flight simulation to provide a corresponding radar display. The terrain engine can include any radar compiler known to those skilled in the art including the Multimode Radar Simulator of The Boeing Company.

The terrain engine 30 is typically comprised of a software program, such as the Terra Vista software package provided by Terrain Experts, Inc., that has been modified to accept and process project source data in addition to terrain source data. The computer software can be executed upon a variety of platforms, including a processor or other types of computing devices.

Regardless of its implementation, the terrain engine 30 can provide the terrain model to the flight simulator 36 in a variety of manners. In one embodiment depicted in Figure 1, the apparatus 10 includes a compression unit 38 for compressing the terrain model, such as by means of wavelet compression or other conventional compression techniques, prior to being transmitted to a remote flight simulator, via either wired or wireless communication links. Upon receipt, a decompression unit 40 decompresses the terrain model and the decompressed terrain model is then stored. During a subsequent flight simulation, the terrain model can be provided to the image generator of the flight simulator in order to generate a realistic image of the area in which the mission route will be flown.

In order to further increase the efficiency with which the method and apparatus 10 of the present invention automatically generate the terrain model, the

apparatus can be configured as depicted in Figure 7 in order to perform a variety of the functions in parallel. In this regard, the apparatus can include a plurality of search engines **24** disposed in parallel for concurrently searching a plurality of different electronic collections **25** of terrain source data. Additionally, the apparatus can include a plurality of parallel image engines **28** in order to concurrently perform different image processing functions. Still further, the apparatus can include a plurality of terrain engines **30** for compiling or combining the terrain source data and the project source data for a variety of different terrain models at the same time. In addition to increasing the efficiency with which terrain models can be generated, the embodiment of the apparatus depicted in Figure 7 is scalable so that additional search, image and terrain engines can be added as the demand increases. In addition, the search, image and terrain engines are preferably hot swappable in order to permit continuous processing, even in instances in which one of the engines fails.

As also depicted in Figure 7, the method and apparatus **10** can include a resource manager **42**, also typically embodied by a computer program that is executed by a processor or other computing device, for allocating or scheduling the plurality of tasks to different ones of the search, image and terrain engines. In this regard, the resource manager typically receives the definition of the areas for which terrain source data is required and the respective resolutions of different regions within the areas from the mission profiler **14**. The resource manager includes a queue **44** for maintaining a prioritized list of the plurality of tasks required to generate a terrain model for each area defined by the mission profiler. These tasks include identifying terrain source data covering each of the areas, processing the terrain source data and compiling the processed data and any project source data to generate respective terrain models. Additionally, the resource manager includes a task pipeline **46** for assigning respective tasks to different ones of the search, image and terrain engines in order to perform the respective tasks in the most efficient manner as known to those skilled in the art.

As a result of the automatic generation of the terrain model, the method and apparatus **10** of the present invention permit the terrain model to be more efficiently generated with substantially less manual participation than conventional techniques. Additionally, the resulting terrain model should be of the highest quality since the terrain source data that is most acceptable, typically by being of

the highest quality and/or the most recent, is collected and compiled to create the terrain model. Moreover, the terrain model may also be partially based upon project source data to further improve the realistic appearance of the resulting terrain model.

5 Many modifications and other embodiments of the invention will come to mind to one skilled in the art to which this invention pertains having the benefit of the teachings presented in the foregoing descriptions and the associated drawings. Therefore, it is to be understood that the invention is not to be limited to the specific embodiments disclosed and that modifications and other embodiments are
10 intended to be included within the scope of the appended claims. Although specific terms are employed herein, they are used in a generic and descriptive sense only and not for purposes of limitation.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2